

## Production Specification

<b>Product Name</b>	PVC Protection Tape	
<b>Part number</b>	3583350	
<b>Application</b>	Easy to tear. No residue. Applicable to mark, artwork, paint. Excellent for protection of metal surface	
<b>Name of backing</b>	SPVC (embossed film)	
<b>Spec. of backing</b>	0.13mm (thickness) x 1330mm (width) x 1000 M (length)	
<b>Color</b>	Yellow	
<b>Type of adhesive</b>	Rubber based adhesive	
<b>Coating thickness</b>	15 ~ 17 $\mu$	
<b>TEST ITEM</b>	<b>UNIT</b>	<b>SPECIFICATION</b>
Total thickness	mm	0.140 +/- 0.017
Adhesion	kg / 25mm	0.350 $\uparrow$
Adhesion to backing	kg / 25mm	
Initial tack	# of rolling ball	20 $\uparrow$
Holding power	minute	60 $\uparrow$
Tensile strength	kg / 25mm	3 $\uparrow$
Elongation	%	100 $\uparrow$
Breakdown Volt.	Unit	
Volume resistivity	$\Omega$ -cm	
<b>Remark :</b>	Finished product specification: The following widths can be adjusted and cut: 50mm, 75mm. The log rolls can be wound into length of 33M.	