

For Pros® Maskeringstejp UV 15 dagar



- Good adhesiveness on smooth surfaces
- UV resistance up to 15 days
- Residue-free removal
- Removable without tearing
- Easy to unwind
- Hand tearable

Blue masking tape, specially designed for outdoor use in the building and construction industries, as well as for do-it-yourself applications. UV resistance up to 15 days. Recommended dry removal.

TECHNICAL PROPERTIES		tolerance	test method
Adhesive:	water-based acrylic emulsion		
Total thickness:	130 µm	± 10 %	AFERA 5006
Adhesion to steel:	min. 1,3 N/cm		AFERA 5001
Tensile strength:	min. 38 N/cm		AFERA 5004
Elongation at break:	min. 8 %		AFERA 5004
Colour:	blue		

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

RECOMMENDATIONS

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.