



## For Pros® Maskeringstejp Standard

- Good adhesiveness on irregular surfaces
- Residue-free removal
- Saturated paper for maximum conformability
- Compatible with the most common paints
- Removable without tearing
- High tack cross-linked adhesive

Professional masking tape for the automotive and car body repair industries; suitable for applications that require resistance to high temperatures (up to 80 °C for 1 hour / up to 100 °C for 20 minutes). Natural rubber adhesive with plasticizing, antioxidant and solvent resins.

TECHNICAL PROPERTIES	tolerance	test method
Backing:	100 µm saturated white paper	
Adhesive:	natural rubber and plasticizing, antioxidant and solvent resins	
Total thickness:	125 µm	± 10 %
Adhesion to steel:	min. 2,2 N/cm	AFERA 5006
Tensile strength:	min. 28 N/cm	AFERA 5001
Elongation at break:	min. 7 %	AFERA 5004
Temperature resistance:	up to 80 °C for 1 h / up to 100 °C for 20 min	AFERA 5004
Colour:	white and yellow	

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

### RECOMMENDATIONS

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.